(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 25 August 2005 (25.08.2005)

PCT

(10) International Publication Number WO 2005/076920 A3

(51) International Patent Classification⁷: B29C 45/14

(21) International Application Number:

PCT/US2005/003553

(22) International Filing Date: 4 February 2005 (04.02.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(**30**) **Priority Data:** 60/541,975

5 February 2004 (05.02.2004) US

(71) Applicant (for all designated States except US):
LOMONT MOLDING, INC. [US/US]; 1516 East
Mapleleaf Drive, P.O. Box 601, Mt. Pleasant, IA 52641
(US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): WATSON, Virgil,

A. [US/US]; 1516 East Mapleleaf Drive, P.O. Box 601, Mt. Pleasant, IA 52641 (US). **BENDER, Jason** [US/US]; 1516 East Mapleleaf Drive, P.O. Box 601, Mt. Pleasant, IA 52641 (US).

- (74) Agents: ZARLEY, Timothy, J. et al.; Capital Square, 400 Locust Street, Suite 200, Des Moines, IA 50309-2350 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: SIGNAGE CONSTRUCTION METHOD AND APPARATUS



(57) Abstract: A sign (20) for viewing by persons in a traffic area accessible by the random passage of persons through the area, the sign (20) including a label (22) formed of a thin layer of plastic material upon which the subject matter of the desired sign is printed. A planar substrate (24) of molded material is fused to the label (22). The planar substrate (24) includes a mounting feature (26) adapted to secure the sign (20) to a second object. During manufacture, an injection device (46) and ejector system (50) are associated with a first sign mold portion, a label is placed in a second sign mold portion, the first and second sign mold portions are closed together during injection, and the previously formed sign is removed from the first sign mold portion via the ejector system (50) prior to closing the mold portions together.

WO 2005/076920 A3



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

(88) Date of publication of the international search report: 17 November 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.